

TEAM[®] Industrial Services

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	PRI-102N
Registration number	-
Synonyms	None.
Product code	807-0006
Issue date	15-November-2012
Version number	01
Revision date	15-November-2012
Supersedes date	13-January-2012

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Industrial Leak Sealant
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name	Team Industrial Services, Inc.
Address	Postbus 37 4380 AA Vlissingen 3237 The Netherlands
Telephone	+31 (0) 118 48 58 00 Fax +31 (0) 118 48 58 86
e-mail	Not available.
Contact person	Not available.

1.4. Emergency telephone number	+1 703-527-3887
---------------------------------	-----------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

This preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification	R10, Muta. Cat. 3;R68, T;R24/25, C;R34, Xn;R20
----------------	--

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 3	H226 - Flammable liquid and vapour.
-------------------	------------	-------------------------------------

Health hazards

Acute toxicity, oral	Category 4	H302 - Harmful if swallowed.
Skin corrosion/irritation	Category 1B	H314 - Causes severe skin burns and eye damage.
Germ cell mutagenicity	Category 2	H341 - Suspected of causing genetic defects.

Hazard summary

Physical hazards	Flammable.
Health hazards	Harmful by inhalation. Toxic in contact with skin and if swallowed. Causes burns. Possible risk of irreversible effects. Occupational exposure to the substance or mixture may cause adverse health effects.
Environmental hazards	Not classified for hazards to the environment.
Specific hazards	May cause lung oedema. May cause damage to the liver and kidneys. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

Main symptoms Unconsciousness. Coughing. Shortness of breath. Discomfort in the chest. Irritation of nose and throat. Symptoms include itching, burning, redness and tearing. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Phenol, m-Cresol, p-Cresol

Hazard pictograms



Signal word Danger

Hazard statements
 H226 - Flammable liquid and vapour.
 H302 - Harmful if swallowed.
 H314 - Causes severe skin burns and eye damage.
 H341 - Suspected of causing genetic defects.

Precautionary statements

Prevention P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Response
 P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage P405 - Store locked up.

Disposal P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information Contains Hexamethylenetetramine. May produce an allergic reaction.

2.3. Other hazards Not assigned.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Phenol, polymer with formaldehyde	40 - 60	9003-35-4 500-005-2	-	-	
Classification:	DSD: -				
	CLP: -				
Graphite	3 - 7	7782-42-5 231-955-3	-	-	
Classification:	DSD: -				
	CLP: -				
m-Cresol	1 - 5	108-39-4 203-577-9	-	604-004-00-9	#
Classification:	DSD: T;R24/25, C;R34				
	CLP: Acute Tox. 3;H301, Acute Tox. 3;H311, Skin Corr. 1B;H314				
Phenol	3 - < 5	108-95-2 203-632-7	-	604-001-00-2	#
Classification:	DSD: Muta. Cat. 3;R68, T;R23/24/25, C;R34, Xn;R48/20/21/22				
	CLP: Acute Tox. 3;H301, Acute Tox. 3;H311, Skin Corr. 1B;H314, Acute Tox. 3;H331, Muta. 2;H341, STOT RE 2;H373				

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
p-Cresol	1 - < 3	106-44-5 203-398-6	-	604-004-00-9	#
Classification:	DSD: T;R24/25, C;R34				
	CLP: Acute Tox. 3;H301, Acute Tox. 3;H311, Skin Corr. 1B;H314				
Amorphous silica gel	3 - 7	63231-67-4 231-545-4	-	-	
Classification:	DSD: -				
	CLP: -				
Water	1- 5	7732-18-5 231-791-2	-	-	
Classification:	DSD: -				
	CLP: -				
Ethylphenol	< 1	25429-37-2 -	-	-	
Classification:	DSD: -				
	CLP: -				
Hexamethylenetetramine	< 1	100-97-0 202-905-8	-	612-101-00-2	
Classification:	DSD: F;R11, R43				
	CLP: Flam. Sol. 2;H228, Skin Sens. 1;H317				
Synthetic hydrocarbons	< 1	N/A -	-	-	
Classification:	DSD: -				
	CLP: -				
Xylenol	< 1	1300-71-6 215-089-3	-	604-006-00-X	
Classification:	DSD: T;R24/25, C;R34, N;R51/53				
	CLP: Acute Tox. 3;H301, Acute Tox. 3;H311, Skin Corr. 1B;H314, Eye Dam. 1;H318, Aquatic Chronic 2;H411				
Formaldehyde	< 0,1	50-00-0 200-001-8	-	605-001-00-5	
Classification:	DSD: Carc. Cat. 3;R40, T;R23/24/25, C;R34, R43				
	CLP: Acute Tox. 3;H301, Acute Tox. 3;H311, Skin Corr. 1B;H314, Skin Sens. 1;H317, Acute Tox. 3;H331, STOT SE 3;H335, Carc. 2;H351				
Silica	< 0,1	14808-60-7 238-878-4	-	-	
Classification:	DSD: -				
	CLP: -				

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
o-Cresol	< 0,1	95-48-7 202-423-8	-	604-004-00-9	#
Classification:	DSD: T;R24/25, C;R34				
	CLP: Acute Tox. 3;H301, Acute Tox. 3;H311, Skin Corr. 1B;H314				

#: This substance has workplace exposure limit(s).

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

Composition comments The full text for all R- and H-phrases is displayed in section 16. All concentrations are in percent by weight.

SECTION 4: First aid measures

General information Chemical burns must be treated by a physician.

4.1. Description of first aid measures

Inhalation If breathing stops, provide artificial respiration. Get medical attention immediately.

Skin contact Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately.

Eye contact Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Only induce vomiting at the instruction of medical personnel. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed Symptoms include itching, burning, redness, and tearing of eyes. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards Flammable liquid and vapour. Heated material: If heated, volume and pressure increases strongly, resulting in explosion of container.

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing media No restrictions known.

5.2. Special hazards arising from the substance or mixture Solvent vapours may form explosive mixtures with air. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

Special fire fighting procedures Ventilate closed spaces before entering them. Containers should be cooled with water to prevent vapor pressure build up. Prevent runoff from fire control or dilution from entering streams, sewers or drinking water supply. Evacuate area and fight fire from a safe distance. Stop leak if you can do so without risk. Move containers from fire area if you can do it without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Avoid inhalation of vapours and contact with skin and eyes. Extinguish all ignition sources. Avoid sparks, flames and smoking. Ventilate. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8.

For emergency responders Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Prevent further leakage or spillage if safe to do so. Do not contaminate water. Environmental manager must be informed of all major spillages.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Clean contaminated surface thoroughly. Sweep up or vacuum up spillage and collect in suitable container for disposal. Never return spills in original containers for re-use. This material and its container must be disposed of as hazardous waste. Collect and dispose of spillage as indicated in Section 13.

6.4. Reference to other sections

See Section 8 for personal protective equipment. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid inhalation of vapours and contact with skin and eyes. Use only with adequate ventilation. Avoid contact during pregnancy/while nursing. The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures. Vapours are heavier than air and may travel along the floor and in the bottom of containers. Use personal protective equipment as required.

7.2. Conditions for safe storage, including any incompatibilities

Follow rules for flammable liquids. Keep away from heat, spark, open flames and other sources of ignition. Keep away from sources of ignition - No smoking. Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials.

7.3. Specific end use(s)

Industrial Leak Sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
Amorphous silica gel (CAS 63231-67-4)	MAK	4 mg/m ³	Inhalable fraction.
Ethanol (CAS 64-17-5)	Ceiling	3800 mg/m ³	
	MAK	2000 ppm	
		1900 mg/m ³	
		1000 ppm	
Formaldehyde (CAS 50-00-0)	Ceiling	0,6 mg/m ³	
		0,5 ppm	
	MAK	0,6 mg/m ³	
		0,5 ppm	
Graphite (CAS 7782-42-5)	MAK	5 mg/m ³	Respirable dust.
	STEL	10 mg/m ³	Respirable dust.
m-Cresol (CAS 108-39-4)	Ceiling	44 mg/m ³	
		10 ppm	
	MAK	22 mg/m ³	
		5 ppm	
p-Cresol (CAS 106-44-5)	Ceiling	44 mg/m ³	
		10 ppm	
	MAK	22 mg/m ³	
		5 ppm	
Phenol (CAS 108-95-2)	MAK	8 mg/m ³	
		2 ppm	
	STEL	6 mg/m ³	
		4 ppm	

Belgium. Exposure Limit Values.

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	TWA	1907 mg/m ³	
		1000 ppm	
Formaldehyde (CAS 50-00-0)	STEL	0,38 mg/m ³	
		0,3 ppm	
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable fraction.
m-Cresol (CAS 108-39-4)	TWA	22 mg/m ³	
		5 ppm	
p-Cresol (CAS 106-44-5)	TWA	22 mg/m ³	
		5 ppm	
Phenol (CAS 108-95-2)	STEL	16 mg/m ³	
		4 ppm	

Belgium. Exposure Limit Values.

Components	Type	Value	Form
	TWA	8 mg/m ³ 2 ppm	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value	Form
Amorphous silica gel (CAS 63231-67-4)	TWA	10 mg/m ³	Inhalable fraction.
		0,07 mg/m ³	Respirable fraction.
Ethanol (CAS 64-17-5)	TWA	1000 mg/m ³	
Formaldehyde (CAS 50-00-0)	STEL	2 mg/m ³	
	TWA	1 mg/m ³	
Graphite (CAS 7782-42-5)	TWA	5 mg/m ³	Inhalable fraction.
Hexamethylenetetramine (CAS 100-97-0)	TWA	2 mg/m ³	
m-Cresol (CAS 108-39-4)	TWA	22 mg/m ³	
p-Cresol (CAS 106-44-5)	TWA	22 mg/m ³	
Phenol (CAS 108-95-2)	TWA	7,8 mg/m ³	

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value
Amorphous silica gel (CAS 63231-67-4)	TWA	2 mg/m ³
Formaldehyde (CAS 50-00-0)	TWA	3 mg/m ³
		2 ppm
Graphite (CAS 7782-42-5)	TWA	10 mg/m ³
Phenol (CAS 108-95-2)	TWA	19 mg/m ³ 5 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value	Form
Amorphous silica gel (CAS 63231-67-4)	TWA	4 mg/m ³	Dust.
Ethanol (CAS 64-17-5)	Ceiling	3000 mg/m ³	
	TWA	1000 mg/m ³	
Formaldehyde (CAS 50-00-0)	Ceiling	1 mg/m ³	
	TWA	0,5 mg/m ³	
Graphite (CAS 7782-42-5)	TWA	10 mg/m ³	Total dust.
		10 mg/m ³	Respirable dust.
m-Cresol (CAS 108-39-4)	Ceiling	40 mg/m ³	
	TWA	20 mg/m ³	
p-Cresol (CAS 106-44-5)	Ceiling	40 mg/m ³	
	TWA	20 mg/m ³	
Phenol (CAS 108-95-2)	Ceiling	15 mg/m ³	
	TWA	7,5 mg/m ³	
Phenol, polymer with formaldehyde (CAS 9003-35-4)	TWA	5 mg/m ³	Dust.

Denmark. Exposure Limit Values

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	TLV	1900 mg/m ³ 1000 ppm	
Formaldehyde (CAS 50-00-0)	Ceiling	0,4 mg/m ³	
		0,3 ppm	
Graphite (CAS 7782-42-5)	TLV	2,5 mg/m ³	Respirable.
m-Cresol (CAS 108-39-4)	TLV	22 mg/m ³ 5 ppm	
		5 ppm	
p-Cresol (CAS 106-44-5)	TLV	22 mg/m ³ 5 ppm	
		5 ppm	

Denmark. Exposure Limit Values

Components	Type	Value	Form
Phenol (CAS 108-95-2)	TLV	4 mg/m3 1 ppm	

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value	Form
Amorphous silica gel (CAS 63231-67-4)	TWA	2 mg/m3	Respirable dust.
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3 1000 ppm	
	TWA	1000 mg/m3 500 ppm	
Formaldehyde (CAS 50-00-0)	TWA	0,6 mg/m3 0,5 ppm	
Graphite (CAS 7782-42-5)	TWA	5 mg/m3	Dust.
Hexamethylenetetramine (CAS 100-97-0)	STEL	5 mg/m3	
	TWA	3 mg/m3	
m-Cresol (CAS 108-39-4)	TWA	22 mg/m3 5 ppm	
p-Cresol (CAS 106-44-5)	TWA	22 mg/m3 5 ppm	
Phenol (CAS 108-95-2)	STEL	16 mg/m3 4 ppm	
	TWA	8 mg/m3 2 ppm	

Finland. Workplace Exposure Limits

Components	Type	Value
Amorphous silica gel (CAS 63231-67-4)	TWA	5 mg/m3
Ethanol (CAS 64-17-5)	STEL	2500 mg/m3 1300 ppm
	TWA	1900 mg/m3 1000 ppm
Formaldehyde (CAS 50-00-0)	Ceiling	1,2 mg/m3 1 ppm
	TWA	0,37 mg/m3 0,3 ppm
Graphite (CAS 7782-42-5)	TWA	2 mg/m3
m-Cresol (CAS 108-39-4)	STEL	45 mg/m3 10 ppm
	TWA	22 mg/m3 5 ppm
p-Cresol (CAS 106-44-5)	STEL	45 mg/m3 10 ppm
	TWA	22 mg/m3 5 ppm
Phenol (CAS 108-95-2)	STEL	20 mg/m3 5 ppm
	TWA	8 mg/m3 2 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	50-00-0) VLE	9500 mg/m3 5000 ppm	
	VME	1900 mg/m3 1000 ppm	
Formaldehyde (CAS 50-00-0)	VLE	1 ppm	

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value	Form
Graphite (CAS 7782-42-5) m-Cresol (CAS 108-39-4)	VME	0,5 ppm	Respirable fraction.
	VME	2 mg/m3	
	VME	22 mg/m3	
p-Cresol (CAS 106-44-5)	VME	5 ppm	
		22 mg/m3	
Phenol (CAS 108-95-2)	VLE	5 ppm	
		15,6 mg/m3	
		4 ppm	
	VME	7,8 mg/m3	
		2 ppm	

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	TWA	960 mg/m3	
Formaldehyde (CAS 50-00-0)	TWA	500 ppm	
		0,37 mg/m3	
Graphite (CAS 7782-42-5)	TWA	0,3 ppm	Inhalable fraction. Respirable fraction.
		4 mg/m3	
		1,5 mg/m3	

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
Amorphous silica gel (CAS 63231-67-4)	AGW	4 mg/m3	Inhalable fraction.
Ethanol (CAS 64-17-5)	AGW	960 mg/m3	
Graphite (CAS 7782-42-5)	AGW	500 ppm	Respirable fraction. Inhalable fraction.
		3 mg/m3	
Phenol (CAS 108-95-2)	AGW	10 mg/m3	
		8 mg/m3	
		2 ppm	

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Formaldehyde (CAS 50-00-0)	STEL	2,5 mg/m3	
	TWA	2 ppm	
Graphite (CAS 7782-42-5)	TWA	2,5 mg/m3	Respirable. Inhalable
		2 ppm	
m-Cresol (CAS 108-39-4)	TWA	5 mg/m3	
		10 mg/m3	
p-Cresol (CAS 106-44-5)	TWA	22 mg/m3	
		5 ppm	
Phenol (CAS 108-95-2)	STEL	22 mg/m3	
		5 ppm	
		38 mg/m3	
	TWA	10 ppm	
		19 mg/m3	
		5 ppm	

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Ethanol (CAS 64-17-5)	STEL	7600 mg/m3
	TWA	1900 mg/m3
Formaldehyde (CAS 50-00-0)	STEL	0,6 mg/m3
	TWA	0,6 mg/m3
m-Cresol (CAS 108-39-4)	STEL	22 mg/m3
	TWA	22 mg/m3

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
p-Cresol (CAS 106-44-5)	STEL	22 mg/m ³
	TWA	22 mg/m ³
Phenol (CAS 108-95-2)	STEL	16 mg/m ³
	TWA	8 mg/m ³

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	TWA	1900 mg/m ³	
		1000 ppm	
Formaldehyde (CAS 50-00-0)	STEL	1,2 mg/m ³	
		1 ppm	
	TWA	0,4 mg/m ³	
		0,3 ppm	
Graphite (CAS 7782-42-5)	TWA	5 mg/m ³	Total dust. Respirable dust.
		2,5 mg/m ³	
Hexamethylenetetramine (CAS 100-97-0)	TWA	3 mg/m ³	
m-Cresol (CAS 108-39-4)	TWA	22 mg/m ³	
p-Cresol (CAS 106-44-5)	TWA	5 ppm	
		22 mg/m ³	
Phenol (CAS 108-95-2)	TWA	5 ppm	
		4 mg/m ³	
		1 ppm	

Ireland. Occupational Exposure Limits

Components	Type	Value	Form
Amorphous silica gel (CAS 63231-67-4)	TWA	6 mg/m ³	Total inhalable dust.
		2,4 mg/m ³	Respirable dust.
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
		2,5 mg/m ³	
Formaldehyde (CAS 50-00-0)	STEL	2 ppm	
		2,5 mg/m ³	
	TWA	2 ppm	
		2,5 mg/m ³	
Graphite (CAS 7782-42-5)	TWA	4 mg/m ³	Respirable dust. Total inhalable dust.
		10 mg/m ³	
m-Cresol (CAS 108-39-4)	TWA	22 mg/m ³	
		5 ppm	
p-Cresol (CAS 106-44-5)	TWA	22 mg/m ³	
		5 ppm	
Phenol (CAS 108-95-2)	STEL	16 mg/m ³	
		4 ppm	
	TWA	8 mg/m ³	
		2 ppm	

Italy. Occupational Exposure Limits

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
Formaldehyde (CAS 50-00-0)	Ceiling	0,3 ppm	
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable fraction.
m-Cresol (CAS 108-39-4)	TWA	20 mg/m ³	Inhalable fraction and vapor.
p-Cresol (CAS 106-44-5)	TWA	20 mg/m ³	Inhalable fraction and vapor.
Phenol (CAS 108-95-2)	TWA	7,8 mg/m ³	
		2 ppm	

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value	Form
Amorphous silica gel (CAS 63231-67-4)	TWA	1 mg/m ³	
Ethanol (CAS 64-17-5)	TWA	1000 mg/m ³	
Formaldehyde (CAS 50-00-0)	TWA	0,5 mg/m ³	
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Dust.
m-Cresol (CAS 108-39-4)	TWA	22 mg/m ³	
		5 ppm	
p-Cresol (CAS 106-44-5)	TWA	22 mg/m ³	
		5 ppm	
Phenol (CAS 108-95-2)	STEL	16 mg/m ³	
		4 ppm	
	TWA	8 mg/m ³	
		2 ppm	

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	STEL	1900 mg/m ³	
		1000 ppm	
	TWA	1000 mg/m ³	
		500 ppm	
Formaldehyde (CAS 50-00-0)	Ceiling	1 mg/m ³	
		1,2 ppm	
	TWA	0,6 mg/m ³	
		0,5 ppm	
Graphite (CAS 7782-42-5)	TWA	3 mg/m ³	Dust.
Hexamethylenetetramine (CAS 100-97-0)	STEL	5 mg/m ³	
		3 mg/m ³	
m-Cresol (CAS 108-39-4)	TWA	22 mg/m ³	
		5 ppm	
p-Cresol (CAS 106-44-5)	TWA	22 mg/m ³	
		5 ppm	
Phenol (CAS 108-95-2)	STEL	16 mg/m ³	
		4 ppm	
	TWA	8 mg/m ³	
		2 ppm	
Phenol, polymer with formaldehyde (CAS 9003-35-4)	TWA	3 mg/m ³	Dust.

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A

Components	Type	Value
m-Cresol (CAS 108-39-4)	TWA	22 mg/m ³
		5 ppm
p-Cresol (CAS 106-44-5)	TWA	22 mg/m ³
		5 ppm
Phenol (CAS 108-95-2)	STEL	16 mg/m ³
		4 ppm
	TWA	8 mg/m ³
		2 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
m-Cresol (CAS 108-39-4)	TWA	22 mg/m ³
		5 ppm
p-Cresol (CAS 106-44-5)	TWA	22 mg/m ³
		5 ppm
Phenol (CAS 108-95-2)	TWA	7,8 mg/m ³
		2 ppm

Netherlands. OELs (binding)

Components	Type	Value
Ethanol (CAS 64-17-5)	STEL	1900 mg/m ³
	TWA	260 mg/m ³
Formaldehyde (CAS 50-00-0)	STEL	0,5 mg/m ³
	TWA	0,15 mg/m ³
Phenol (CAS 108-95-2)	TWA	8 mg/m ³

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value	Form
Amorphous silica gel (CAS 63231-67-4)	TLV	1,5 mg/m ³	Respirable dust.
Ethanol (CAS 64-17-5)	TLV	950 mg/m ³ 500 ppm	
Formaldehyde (CAS 50-00-0)	Ceiling	1,2 mg/m ³	
	TLV	1 ppm 0,6 mg/m ³ 0,5 ppm	
Graphite (CAS 7782-42-5)	TLV	2 mg/m ³ 10 mg/m ³	Respirable dust. Total dust.
Hexamethylenetetramine (CAS 100-97-0)	TLV	3 mg/m ³	
m-Cresol (CAS 108-39-4)	TLV	22 mg/m ³ 5 ppm	
p-Cresol (CAS 106-44-5)	TLV	22 mg/m ³ 5 ppm	
Phenol (CAS 108-95-2)	STEL	12 mg/m ³ 3 ppm	
	TLV	4 mg/m ³ 1 ppm	

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	TWA	1900 mg/m ³	
Formaldehyde (CAS 50-00-0)	STEL	1 mg/m ³	
	TWA	0,5 mg/m ³	
Graphite (CAS 7782-42-5)	TWA	4 mg/m ³ 1 mg/m ³	Total dust. Respirable dust.
Hexamethylenetetramine (CAS 100-97-0)	TWA	4 mg/m ³	
m-Cresol (CAS 108-39-4)	TWA	22 mg/m ³	
p-Cresol (CAS 106-44-5)	TWA	22 mg/m ³	
Phenol (CAS 108-95-2)	STEL	16 mg/m ³	
	TWA	7,8 mg/m ³	

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
Phenol (CAS 108-95-2)	TWA	7,8 mg/m ³ 2 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	TWA	1000 ppm	
Formaldehyde (CAS 50-00-0)	Ceiling	0,3 ppm	
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable fraction.
m-Cresol (CAS 108-39-4)	TWA	5 ppm	
p-Cresol (CAS 106-44-5)	TWA	5 ppm	
Phenol (CAS 108-95-2)	TWA	5 ppm	

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
Ethanol (CAS 64-17-5)	STEL	9500 mg/m ³
		5000 ppm
	TWA	1900 mg/m ³
Formaldehyde (CAS 50-00-0)		1000 ppm
	STEL	3 mg/m ³
		2 ppm
m-Cresol (CAS 108-39-4)		1,2 mg/m ³
	TWA	1 ppm
		22 mg/m ³
p-Cresol (CAS 106-44-5)		5 ppm
	TWA	22 mg/m ³
		5 ppm
Phenol (CAS 108-95-2)		7,8 mg/m ³
	TWA	2 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value	Form
Amorphous silica gel (CAS 63231-67-4)	TWA	0,3 mg/m ³	
Ethanol (CAS 64-17-5)	TWA	960 mg/m ³	
		500 ppm	
Formaldehyde (CAS 50-00-0)	TWA	0,37 mg/m ³	
		0,3 ppm	
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable fraction. Total
		10 mg/m ³	
		22 mg/m ³	
m-Cresol (CAS 108-39-4)	TWA	5 ppm	
		22 mg/m ³	
		5 ppm	
p-Cresol (CAS 106-44-5)	TWA	22 mg/m ³	
		5 ppm	
		8 mg/m ³	
Phenol (CAS 108-95-2)	TWA	2 ppm	

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value	Form
Amorphous silica gel (CAS 63231-67-4)	TWA	4 mg/m ³	Inhalable fraction.
Ethanol (CAS 64-17-5)	TWA	1900 mg/m ³	
		1000 ppm	
Formaldehyde (CAS 50-00-0)	TWA	0,62 mg/m ³	
		0,5 ppm	
m-Cresol (CAS 108-39-4)	TWA	22 mg/m ³	
		5 ppm	
		22 mg/m ³	
p-Cresol (CAS 106-44-5)	TWA	5 ppm	
		22 mg/m ³	
		8 mg/m ³	
Phenol (CAS 108-95-2)	TWA	2 ppm	

Spain

Components	Type	Value	Form
Graphite (CAS 7782-42-5)	TWA (VLA-ED)	2 mg/m ³	Dust.

Spain. Occupational Exposure Limits

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	TWA	1910 mg/m ³	
		1000 ppm	
		0,37 mg/m ³	
Formaldehyde (CAS 50-00-0)	STEL	0,3 ppm	
		2 mg/m ³	Dust.
Graphite (CAS 7782-42-5)	TWA		

Spain. Occupational Exposure Limits

Components	Type	Value	Form
m-Cresol (CAS 108-39-4)	TWA	22 mg/m3 5 ppm	
p-Cresol (CAS 106-44-5)	TWA	22 mg/m3 5 ppm	
Phenol (CAS 108-95-2)	STEL	16 mg/m3 4 ppm	
	TWA	8 mg/m3 2 ppm	

Sweden. Occupational Exposure Limit Values

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3 1000 ppm	
	TWA	1000 mg/m3 500 ppm	
Formaldehyde (CAS 50-00-0)	Ceiling	0,74 mg/m3 0,6 ppm	
	TWA	0,37 mg/m3 0,3 ppm	
Graphite (CAS 7782-42-5)	TWA	0,2 fibers/mL 5 mg/m3	Total dust.
	STEL	5 mg/m3	
Hexamethylenetetramine (CAS 100-97-0)	TWA	3 mg/m3	
	STEL	9 mg/m3	
m-Cresol (CAS 108-39-4)	TWA	2 ppm	
	TWA	4,5 mg/m3 1 ppm	
p-Cresol (CAS 106-44-5)	STEL	9 mg/m3 2 ppm	
	TWA	4,5 mg/m3 1 ppm	
Phenol (CAS 108-95-2)	STEL	8 mg/m3 2 ppm	
	TWA	4 mg/m3 1 ppm	

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3 1000 ppm	
	TWA	960 mg/m3 500 ppm	
Formaldehyde (CAS 50-00-0)	STEL	0,74 mg/m3 0,6 ppm	
	TWA	0,37 mg/m3 0,3 ppm	
Graphite (CAS 7782-42-5)	TWA	5 mg/m3 2,5 mg/m3	Inhalable dust. Respirable dust.
	STEL	22 mg/m3	
m-Cresol (CAS 108-39-4)	TWA	5 ppm 22 mg/m3	
	TWA	5 ppm 22 mg/m3	
p-Cresol (CAS 106-44-5)	STEL	22 mg/m3 5 ppm	
	TWA	22 mg/m3 5 ppm	
Phenol (CAS 108-95-2)	STEL	19 mg/m3 5 ppm	
	TWA	19 mg/m3	

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
		5 ppm	

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
Amorphous silica gel (CAS 63231-67-4)	TWA	6 mg/m ³	Inhalable dust.
Ethanol (CAS 64-17-5)	TWA	2,4 mg/m ³ 1920 mg/m ³ 1000 ppm	Respirable dust.
Formaldehyde (CAS 50-00-0)	STEL	2,5 mg/m ³	
	TWA	2 ppm 2,5 mg/m ³	
Graphite (CAS 7782-42-5)	TWA	2 ppm 4 mg/m ³	Respirable dust.
Phenol (CAS 108-95-2)	STEL	16 mg/m ³	
	TWA	4 ppm 7,8 mg/m ³ 2 ppm	

United Kingdom

Components	Type	Value	Form
Graphite (CAS 7782-42-5)	TWA	10 mg/m ³	Inhalable dust.

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
m-Cresol (CAS 108-39-4)	TWA	22 mg/m ³ 5 ppm
p-Cresol (CAS 106-44-5)	TWA	22 mg/m ³ 5 ppm
Phenol (CAS 108-95-2)	STEL	16 mg/m ³ 4 ppm
	TWA	8 mg/m ³ 2 ppm

Biological limit values**Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV) , Social Affairs and Ministry of Health**

Components	Value	Determinant	Specimen	Sampling time
Phenol (CAS 108-95-2)	1,3 mmol/l	Total phenol	Urine	*

* - For sampling details, please see the source document.

France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065)

Components	Value	Determinant	Specimen	Sampling time
Phenol (CAS 108-95-2)	250 mg/g	Phenol total	Creatinine in urine	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling time
Phenol (CAS 108-95-2)	300 mg/l	Phenol	Urine	*

* - For sampling details, please see the source document.

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling time
Amorphous silica gel (CAS 63231-67-4)	25 %	red blood cell or total blood acetylcholinesterase activity (EC. 3.1.1.7.)	Reduction from individual baseline activity in red blood cells	*

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling time
Ethanol (CAS 64-17-5)	25 %	red blood cell or total blood acetylcholinest erase activity (EC. 3.1.1.7.)	Reduction from individual baseline activity in red blood cells	*
Formaldehyde (CAS 50-00-0)	25 %	red blood cell or total blood acetylcholinest erase activity (EC. 3.1.1.7.)	Reduction from individual baseline activity in red blood cells	*
m-Cresol (CAS 108-39-4)	25 %	red blood cell or total blood acetylcholinest erase activity (EC. 3.1.1.7.)	Reduction from individual baseline activity in red blood cells	*
p-Cresol (CAS 106-44-5)	25 %	red blood cell or total blood acetylcholinest erase activity (EC. 3.1.1.7.)	Reduction from individual baseline activity in red blood cells	*
Phenol (CAS 108-95-2)	300 mg/g	Phenol	Creatinine in urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Specimen	Sampling time
Phenol (CAS 108-95-2)	250 mg/g	Creatinine in urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Not available.

Derived no-effect level (DNEL)

Components	Type	Route	Value	Form
Ethanol (CAS 64-17-5)	Workers	Dermal	343 mg/kg/day	Long term Systemic effects
		Inhalation	950 mg/m3	Long term Systemic effects
Formaldehyde (CAS 50-00-0)	Workers	Inhalation	1900 mg/m3	Acute Local effects
		Dermal	240 mg/kg/day	Long term Systemic effects
		Inhalation	9 mg/m3	Long term Systemic effects
		Inhalation	1 mg/m3	Acute Local effects
Graphite (CAS 7782-42-5)	Workers	Inhalation	0,5 mg/m3	Long term Local effects
		Inhalation	1,2 mg/m3	Long term exposure local effects
		Dermal	8,8 mg/kg/day	Long term Systemic effects
Hexamethylenetetramine (CAS 100-97-0)	Workers	Dermal	229 mg/kg/day	Acute Systemic effects
		Inhalation	31 mg/m3	Long term Systemic effects
		Inhalation	1400 mg/m3	Acute Systemic effects
m-Cresol (CAS 108-39-4)	Workers	Inhalation	343 mg/m3	Acute Systemic effects
		Inhalation	3,5 mg/m3	Long term Systemic effects
		Inhalation	0,9 mg/m3	Acute Local effects

Components	Type	Route	Value	Form
p-Cresol (CAS 106-44-5)	Workers	Inhalation	0,9 mg/m3	Long term Local effects
		Inhalation	3,5 mg/m3	Long term Systemic effects
		Inhalation	233 mg/m3	Acute Systemic effects
		Inhalation	0,9 mg/m3	Acute Local effects
		Inhalation	0,9 mg/m3	Long term exposure local effects
Phenol (CAS 108-95-2)	Workers	Inhalation	343 mg/m3	Acute exposure systemic effect
		Inhalation	3,5 mg/m3	Long term exposure systemic effects
		Inhalation	0,9 mg/m3	Acute exposure local effects
		Inhalation	0,9 mg/m3	Long term exposure local effects

Predicted no effect concentrations (PNECs)

Components	Type	Route	Value	Form
Ethanol (CAS 64-17-5)	Aqua (freshwater)	Not applicable	0,96 mg/l	
	Aqua (intermittent releases)	Not applicable	2,75 mg/l	
	Aqua (marine water)	Not applicable	0,79 mg/l	
	Oral	Not applicable	0,72 g/kg	
	Sediment (freshwater)	Not applicable	3,6 mg/kg	
	Sewage Treatment Plant	Not applicable	580 mg/l	
	Soil	Not applicable	0,63 mg/kg	
Formaldehyde (CAS 50-00-0)	Aqua (freshwater)	Not applicable	0,47 mg/l	
	Aqua (intermittent releases)	Not applicable	4,7 mg/l	
	Aqua (marine water)	Not applicable	0,47 mg/l	
	Sediment (freshwater)	Not applicable	2,44 mg/kg	
	Sediment (marine water)	Not applicable	2,44 mg/kg	
	Sewage Treatment Plant	Not applicable	0,19 mg/l	
	Soil	Not applicable	0,21 mg/kg	
Hexamethylenetetramine (CAS 100-97-0)	Aqua (freshwater)	Not applicable	3 mg/l	
	Aqua (intermittent releases)	Not applicable	30 mg/l	
	Aqua (marine water)	Not applicable	0,5 mg/l	
	Oral	Not applicable	0,05 g/kg	
	Sediment (freshwater)	Not applicable	11 mg/kg	
	Sediment (marine water)	Not applicable	1,84 mg/kg	
	Sewage Treatment Plant	Not applicable	100 mg/l	
m-Cresol (CAS 108-39-4)	Soil	Not applicable	0,58 mg/kg	
	Aqua (freshwater)	Not applicable	0,1 mg/l	
	Aqua (intermittent releases)	Not applicable	0,076 mg/l	
	Aqua (marine water)	Not applicable	0,01 mg/l	
	Sediment (freshwater)	Not applicable	0,154 mg/kg	
	Sewage Treatment Plant	Not applicable	1,14 mg/l	
	Soil	Not applicable	0,073 mg/kg	
p-Cresol (CAS 106-44-5)	Aqua (freshwater)	Not applicable	0,03 mg/l	
	Aqua (intermittent releases)	Not applicable	0,044 mg/l	
	Aqua (marine water)	Not applicable	0,003 mg/l	

Components	Type	Route	Value	Form
Phenol (CAS 108-95-2)	Sediment (freshwater)	Not applicable	0,055 mg/kg	
	Sewage Treatment Plant	Not applicable	1,65 mg/l	
	Soil	Not applicable	0,029 mg/kg	
	Aqua (freshwater)	Not applicable	0,1 mg/l	
	Aqua (intermittent releases)	Not applicable	0,076 mg/l	
	Aqua (marine water)	Not applicable	0,01 mg/l	
	Sediment (freshwater)	Not applicable	0,154 mg/kg	
	Sewage Treatment Plant	Not applicable	1,14 mg/l	
	Soil	Not applicable	0,073 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Observe occupational exposure limits and minimise the risk of exposure. An eye wash and safety shower should be available in the immediate work area. Use explosion-proof equipment.

Individual protection measures, such as personal protective equipment

General information

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

- Hand protection

Wear suitable gloves. Butyl rubber gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable.

- Other

Wear appropriate clothing to prevent possibility of skin contact.

Respiratory protection

In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P2).

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls

Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Black pliable semi-solid with phenolic odor.
Physical state	Liquid.
Form	Paste.
Colour	Black.
Odour	Phenolic.
Odour threshold	0,003 - 5 ppm (m-Cresol)
pH	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	33,3 °C (92 °F) ASTM D3278 Setflash E.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	Not available.

Solubility(ies)	Not available.
Partition coefficient (n-octanol/water)	No data available.
Decomposition temperature	537,8 °C (1000 °F)
Viscosity	Not applicable.
Explosive properties	Not available.
Oxidizing properties	Not available.
9.2. Other information	No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	Hazardous polymerisation does not occur.
10.4. Conditions to avoid	Flames and sparks. Avoid static discharge and uncontrolled exposure to high temperatures. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidizers, strong acids, and strong bases. Strong reducing agents.
10.6. Hazardous decomposition products	Carbon oxides. Formaldehyde. Nitrogen oxides (NOx). Silicon dioxide.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Ingestion	Harmful if swallowed.
Inhalation	May cause respiratory tract irritation.
Skin contact	Causes severe skin burns.
Eye contact	Causes severe eye burns.

Symptoms Corrosive. Prolonged contact causes serious eye and tissue damage. Prolonged or repeated inhalation/ingestion may cause central nervous system, blood, lung, liver or kidney damage.

11.1. Information on toxicological effects

Acute toxicity Harmful if swallowed. Causes burns. Contains material which may cause lung, liver, kidney, heart, blood and central nervous system damage.

Components	Species	Test results
Formaldehyde (CAS 50-00-0)		
Acute		
<i>Inhalation</i>		
LC50	Rat	0,48 mg/l, 4 Hours
m-Cresol (CAS 108-39-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	620 mg/kg
<i>Oral</i>		
LD50	Rat	242 mg/kg
p-Cresol (CAS 106-44-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	300 mg/kg
<i>Oral</i>		
LD50	Rat	207 mg/kg
Phenol (CAS 108-95-2)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	850 mg/kg
<i>Oral</i>		
LD50	Rat	530 mg/kg

Skin corrosion/irritation Causes severe skin burns.

Serious eye damage/irritation	Causes severe eye burns.
Respiratory sensitisation	No data available.
Skin sensitisation	The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals in contact with skin.
Germ cell mutagenicity	Suspected of causing genetic defects.
Carcinogenicity	Contains a substance which may be potentially carcinogenic.

IARC Monographs. Overall Evaluation of Carcinogenicity

Formaldehyde (CAS 50-00-0)	1 Carcinogenic to humans.
Phenol (CAS 108-95-2)	3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity	No data available.
Specific target organ toxicity - single exposure	Not available.
Specific target organ toxicity - repeated exposure	Not available.
Aspiration hazard	Not available.
Mixture versus substance information	Not available.
Other information	Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure.

SECTION 12: Ecological information

12.1. Toxicity The product contains a substance which may be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

Components	Species		Test results
Formaldehyde (CAS 50-00-0)	Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia pulex</i>)	4,3 - 7,8 mg/l, 48 hours
Fish	LC50	American eel (<i>Anguilla rostrata</i>)	0 - 197,79 mg/l, 96 hours
Hexamethylenetetramine (CAS 100-97-0)	Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	29868 - 43390 mg/l, 48 hours
Fish	LC50	Bleak (<i>Alburnus alburnus</i>)	> 10000 mg/l, 96 hours
m-Cresol (CAS 108-39-4)	Aquatic		
Crustacea	EC50	Scud (<i>Gammarus fasciatus</i>)	7 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>)	8,9 mg/l, 96 hours
p-Cresol (CAS 106-44-5)	Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	7,7 mg/l, 48 hours
Fish	LC50	Fish (<i>Lepidocephalichthyes guntea</i>)	6,15 - 7,96 mg/l, 96 hours

12.2. Persistence and degradability No data available.

12.3. Bioaccumulative potential No data available.

Partition coefficient n-octanol/water (log Kow) No data available.

Formaldehyde	0,35
Phenol	1,46
p-Cresol	1,94
m-Cresol	1,96

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil Not available.

12.5. Results of PBT and vPvB assessment Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential. The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.
EU waste code	08 04 09*
Disposal methods/information	Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

ADR

14.1. UN number	UN1866
14.2. UN proper shipping name	Resin solution
14.3. Transport hazard class(es)	3
Subsidiary class(es)	-
14.4. Packing group	III
14.5. Environmental hazards	No
Tunnel restriction code	Not available.
Labels required	3
14.6. Special precautions for user	Not available.

RID

14.1. UN number	UN1866
14.2. UN proper shipping name	Resin solution
14.3. Transport hazard class(es)	3
Subsidiary class(es)	-
14.4. Packing group	III
14.5. Environmental hazards	No
Labels required	3
14.6. Special precautions for user	Not available.

ADN

14.1. UN number	UN1866
14.2. UN proper shipping name	Resin solution
14.3. Transport hazard class(es)	3
Subsidiary class(es)	-
14.4. Packing group	III
14.5. Environmental hazards	No
Labels required	3
14.6. Special precautions for user	Not available.

IATA

14.1. UN number	UN1866
14.2. UN proper shipping name	Resin solution
14.3. Transport hazard class(es)	3
Subsidiary class(es)	-
14.4. Packing group	III
14.5. Environmental hazards	Not available.
Labels required	Not available.
ERG Code	3L
14.6. Special precautions for user	Not available.

IMDG

14.1. UN number	UN1866
14.2. UN proper shipping name	Resin solution

14.3. Transport hazard class(es)	3
Subsidiary class(es)	-
14.4. Packing group	III
14.5. Environmental hazards	
Marine pollutant	No
Labels required	Not available.
EmS	F-E, S-E
14.6. Special precautions for user	Not available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 143/2011 Annex XIV Substances Subject to Authorisation

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Hexamethylenetetramine (CAS 100-97-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Not regulated.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding

Formaldehyde (CAS 50-00-0)

Other EU regulations

Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances

Not regulated.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Formaldehyde (CAS 50-00-0)

Hexamethylenetetramine (CAS 100-97-0)

m-Cresol (CAS 108-39-4)

p-Cresol (CAS 106-44-5)

Phenol (CAS 108-95-2)

Directive 94/33/EC on the protection of young people at work

Formaldehyde (CAS 50-00-0)

Hexamethylenetetramine (CAS 100-97-0)

m-Cresol (CAS 108-39-4)

p-Cresol (CAS 106-44-5)
Phenol (CAS 108-95-2)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended and respective national laws implementing EC directives. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006 as amended.

National regulations

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work. Pregnant women should not work with the product, if there is the least risk of exposure. Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

DNEL: Derived No-Effect Level.
PNEC: Predicted No-Effect Concentration. PBT: Persistent, bioaccumulative and toxic. vPvB: Very Persistent and very Bioaccumulative.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R10 Flammable.
R11 Highly flammable.
R20 Harmful by inhalation.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R24/25 Toxic in contact with skin and if swallowed.
R34 Causes burns.
R40 Limited evidence of a carcinogenic effect.
R43 May cause sensitisation by skin contact.
R48/20/21/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R68 Possible risk of irreversible effects.
H228 - Flammable solid.
H301 - Toxic if swallowed.
H311 - Toxic in contact with skin.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H331 - Toxic if inhaled.
H335 - May cause respiratory irritation.
H341 - Suspected of causing genetic defects.
H351 - Suspected of causing cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.

Training information

Follow training instructions when handling this material.

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.