

TEAM[®] Industrial Services

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	L-160
Registration number	-
Synonyms	None.
Product code	900-0010
Issue date	20-March-2013
Version number	01
Revision date	20-March-2013
Supersedes date	07-December-2011

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Industrial Leak Sealant
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name	Team Industrial Services, Inc.
Address	Postbus 37 4380 AA Vlissingen 3237 The Netherlands
Telephone	+31 (0) 118 48 58 00 Fax +31 (0) 118 48 58 86
e-mail	Not available.
Contact person	Not available.

1.4. Emergency telephone number +1 703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification F;R11, Repr. Cat. 3;R63, Xn;R65-48/20, Xi;R38, R67

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 2	H225 - Highly flammable liquid and vapour.
-------------------	------------	--

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Reproductive toxicity (the unborn child)	Category 2	H361d - Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	Category 3 respiratory tract irritation	
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	Category 2 (Central nervous system)	H373 - May cause damage to organs (Central nervous system) through prolonged or repeated exposure.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.


Hazard summary

Physical hazards Highly flammable.

Health hazards	Irritating to skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness. Occupational exposure to the substance or mixture may cause adverse health effects.
Environmental hazards	Not classified for hazards to the environment.
Specific hazards	Causes skin irritation. May cause eye irritation. Prolonged or repeated contact may dry skin and cause dermatitis. Suspected of damaging the unborn child. Vapours may cause drowsiness and dizziness.
Main symptoms	Skin irritation. Irritation of eyes and mucous membranes. Symptoms include itching, burning, redness and tearing. Shortness of breath.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:	Toluene
Hazard pictograms	
Signal word	Danger
Hazard statements	H225 - Highly flammable liquid and vapour. H315 - Causes skin irritation. H361d - Suspected of damaging the unborn child. H373 - May cause damage to organs (Central nervous system) through prolonged or repeated exposure. H336 - May cause drowsiness or dizziness. H304 - May be fatal if swallowed and enters airways.

Precautionary statements

Prevention	P201 - Obtain special instructions before use. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P260 - Do not breathe gas/mist/vapours/spray.
Response	P308 + P313 - IF exposed or concerned: Get medical advice/attention. P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. P331 - Do NOT induce vomiting.
Storage	P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
Disposal	P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information Not applicable.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Toluene	50-80	108-88-3 203-625-9	-	601-021-00-3	#
Classification:	DSD:	F;R11, Repr. Cat. 3;R63, Xn;R65-48/20, Xi;R38, R67			
	CLP:	Flam. Liq. 2;H225, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Repr. 2;H361d, STOT RE 2;H373			
Polymer resin	25-50	N/A	-	-	
Classification:	DSD:	-			
	CLP:	-			

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

#: This substance has been assigned Community workplace exposure limit(s).

Composition comments All concentrations are in percent by weight. The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
4.1. Description of first aid measures	
Inhalation	Move to fresh air. Get medical attention if any discomfort occurs.
Skin contact	Remove contaminated clothing and shoes. Flush thoroughly with water for at least 15 minutes. If irritation occurs, get medical assistance.
Eye contact	Flush thoroughly with water for at least 15 minutes. Get medical attention if irritation develops or persists.
Ingestion	Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Only induce vomiting at the instruction of medical personnel. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately.
4.2. Most important symptoms and effects, both acute and delayed	Skin irritation. Irritation of eyes and mucous membranes. Symptoms include itching, burning, redness, and tearing of eyes.
4.3. Indication of any immediate medical attention and special treatment needed	Be aware that symptoms of chemical pneumonia (shortness of breath) may occur several hours after exposure.

SECTION 5: Firefighting measures

General fire hazards	The product is highly flammable, and explosive vapour/air mixtures may be formed.
5.1. Extinguishing media	
Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	No restrictions known.
5.2. Special hazards arising from the substance or mixture	Solvent vapours may form explosive mixtures with air. By heating and fire, corrosive vapours/gases may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Special fire fighting procedures	In the event of fire, cool tanks with water spray. Move containers from fire area if you can do it without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Ventilate closed spaces before entering. Avoid inhalation of vapours and contact with skin and eyes. Wear appropriate protective equipment and clothing during clean-up. See Section 8 for personal protective equipment.
For emergency responders	Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Prevent further leakage or spillage if safe to do so.
6.3. Methods and material for containment and cleaning up	Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. After removal flush contaminated area thoroughly with water. Never return spills to original containers for re-use. This material and its container must be disposed of as hazardous waste.
6.4. Reference to other sections	For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Pregnant or breastfeeding women must not handle this product. Avoid inhalation of vapours and contact with skin and eyes. Use only with adequate ventilation. Wear approved safety goggles. Wear protective gloves and appropriate clothing to prevent skin contact. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Store in tightly closed original container in a dry, cool and well-ventilated place.
7.3. Specific end use(s)	Industrial Leak Sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List

Components	Type	Value
Toluene (CAS 108-88-3)	MAK	190 mg/m ³
		50 ppm
	STEL	380 mg/m ³
		100 ppm

Belgium. Exposure Limit Values.

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
		100 ppm
	TWA	77 mg/m ³
		20 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
	TWA	192 mg/m ³

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value
Toluene (CAS 108-88-3)	TWA	375 mg/m ³
		100 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	500 mg/m ³
	TWA	200 mg/m ³

Denmark. Exposure Limit Values

Components	Type	Value
Toluene (CAS 108-88-3)	TLV	94 mg/m ³
		25 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
		100 ppm
	TWA	192 mg/m ³
		50 ppm

Finland. Workplace Exposure Limits

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	380 mg/m ³
		100 ppm
	TWA	81 mg/m ³
		25 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Toluene (CAS 108-88-3)	VLE	384 mg/m ³
		100 ppm
	VME	192 mg/m ³
		50 ppm

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
Toluene (CAS 108-88-3)	TWA	190 mg/m ³ 50 ppm

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
Toluene (CAS 108-88-3)	AGW	190 mg/m ³ 50 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	560 mg/m ³ 150 ppm
	TWA	375 mg/m ³ 100 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	380 mg/m ³
	TWA	190 mg/m ³

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	188 mg/m ³ 50 ppm
	TWA	94 mg/m ³ 25 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³ 100 ppm
	TWA	192 mg/m ³ 50 ppm

Italy. OELs

Components	Type	Value
Toluene (CAS 108-88-3)	TWA	192 mg/m ³ 50 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	150 mg/m ³ 40 ppm
	TWA	50 mg/m ³ 14 ppm

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements (Hygiene Norm HN 23:2007)

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³ 100 ppm
	TWA	192 mg/m ³ 50 ppm

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³ 100 ppm
	TWA	192 mg/m ³ 50 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
		100 ppm
	TWA	192 mg/m ³
		50 ppm

Netherlands. OELs (binding)

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
	TWA	150 mg/m ³

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
Toluene (CAS 108-88-3)	TLV	94 mg/m ³
		25 ppm

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	200 mg/m ³
	TWA	100 mg/m ³

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
		100 ppm
	TWA	192 mg/m ³
		50 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
Toluene (CAS 108-88-3)	TWA	50 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
		100 ppm
	TWA	192 mg/m ³
		50 ppm

Slovakia. OELs. Decree of the government of the Slovak Republic concerning protection of health in work with chemical agents

Components	Type	Value
Toluene (CAS 108-88-3)	TWA	192 mg/m ³
		50 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
Toluene (CAS 108-88-3)	TWA	192 mg/m ³
		50 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
		100 ppm
	TWA	192 mg/m ³
		50 ppm

Sweden. Occupational Exposure Limit Values

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
		100 ppm
	TWA	192 mg/m ³
		50 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	760 mg/m ³
		200 ppm
	TWA	190 mg/m ³
		50 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
		100 ppm
	TWA	191 mg/m ³
		50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	384 mg/m ³
		100 ppm
	TWA	192 mg/m ³
		50 ppm

Biological limit values**Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV) , Social Affairs and Ministry of Health**

Components	Value	Determinant	Specimen	Sampling time
Toluene (CAS 108-88-3)	500 nmol/l	Toluene concentration	Blood	*

* - For sampling details, please see the source document.

France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065)

Components	Value	Determinant	Specimen	Sampling time
Toluene (CAS 108-88-3)	2500 mg/g	Acide hippurique	Creatinine in urine	*
	2500 mg/g	Acide hippurique	Creatinine in urine	*
	1 mg/l	Toluène	Venous blood	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling time
Toluene (CAS 108-88-3)	3 mg/l	o-Kresol	Urine	*
	1 mg/l	Toluol	Blood	*

* - For sampling details, please see the source document.

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling time
Toluene (CAS 108-88-3)	1 mg/g	o-crezol	Creatinine in urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Specimen	Sampling time
Toluene (CAS 108-88-3)	600 µg/l	Blood	*
	2 g/g	Creatinine in urine	*

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Specimen	Sampling time
	0,5 mg/l	Urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no-effect level (DNEL)

Components	Type	Route	Value	Form
Toluene (CAS 108-88-3)	Workers	Dermal	384 mg/kg/day	Long term Systemic effects
		Inhalation	384 mg/m ³	Acute Local effects
		Inhalation	384 mg/m ³	Acute Systemic effects
		Inhalation	192 mg/m ³	Long term Local effects
		Inhalation	192 mg/m ³	Long term Systemic effects

Predicted no effect concentrations (PNECs)

Components	Type	Route	Value	Form
Toluene (CAS 108-88-3)	Aqua (freshwater)	Not applicable	0,68 mg/l	
	Aqua (intermittent releases)	Not applicable	0,68 mg/l	
	Aqua (marine water)	Not applicable	0,68 mg/l	
	Sediment (freshwater)	Not applicable	16,39 mg/kg	
	Sediment (marine water)	Not applicable	16,39 mg/kg	
	Sewage Treatment Plant	Not applicable	13,61 mg/l	
	Soil	Not applicable	2,89 mg/kg	

8.2. Exposure controls

Appropriate engineering controls Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

Individual protection measures, such as personal protective equipment

General information	Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Wear approved safety goggles.
Skin protection	
- Hand protection	Wear protective gloves. Polyvinyl alcohol gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.
- Other	Wear appropriate chemical resistant clothing to prevent any possibility of skin contact.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Private clothes and working clothes should be kept separately.

Environmental exposure controls Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Form	Viscous liquid.
Colour	White.
Odour	Solvent.
Odour threshold	0,5 - 23 ppm (Toluene)
pH	Not applicable.

Melting point/freezing point	Not available.
Initial boiling point and boiling range	110 °C (230 °F) (solvent)
Flash point	< 10 °C (< 50 °F)
Evaporation rate	1 (Butyl acetate=1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	6 mm Hg @ 20 °C
Vapour density	Not applicable.
Relative density	0,9
Solubility(ies)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Decomposition temperature	Not available.
Viscosity	Not applicable.
Explosive properties	Not available.
Oxidizing properties	Not available.
9.2. Other information	No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	Hazardous polymerisation does not occur.
10.4. Conditions to avoid	Flames and sparks.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Hydrocarbons. Carbon monoxide. Carbon dioxide. Acrolein. Acids. Ketones. Aldehydes.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Ingestion	May cause discomfort if swallowed.
Inhalation	Vapours may cause drowsiness and dizziness.
Skin contact	Causes skin irritation. Prolonged or repeated contact may dry skin and cause dermatitis. Components of the product may be absorbed into the body through the skin.
Eye contact	May cause eye irritation.

Symptoms Irritation of eyes and mucous membranes. Symptoms include itching, burning, redness and tearing. Skin irritation.

11.1. Information on toxicological effects

Acute toxicity May cause discomfort if swallowed.

Components	Species	Test results
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	14,1 ml/kg
<i>Inhalation</i>		
LC50	Rat	49000 mg/m ³ , 4 Hours
<i>Oral</i>		
LD50	Rat	636 mg/kg
Skin corrosion/irritation	Causes skin irritation. Prolonged or repeated contact may dry skin and cause dermatitis.	
Serious eye damage/irritation	May cause eye irritation.	

Respiratory sensitisation	Not classified.
Skin sensitisation	Not a skin sensitiser.
Germ cell mutagenicity	Not available.
Carcinogenicity	Not classified.

IARC Monographs. Overall Evaluation of Carcinogenicity

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity	Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure: Central nervous system.
Aspiration hazard	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Mixture versus substance information	Not available.
Other information	Not available.

SECTION 12: Ecological information

12.1. Toxicity The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test results
Toluene (CAS 108-88-3)		
Aquatic		
Crustacea	EC50 Water flea (<i>Daphnia magna</i>)	5,46 - 9,83 mg/l, 48 hours
Fish	LC50 Coho salmon, silver salmon (<i>Oncorhynchus kisutch</i>)	5,5 mg/l, 96 hours

12.2. Persistence and degradability No data available.

12.3. Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient n-octanol/water (log Kow)

Toluene (CAS 108-88-3) 2,73

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil Not available.

Mobility in general The product has poor water-solubility. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.
EU waste code	08 04 09*
Disposal methods/information	Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

ADR

14.1. UN number	UN1294
14.2. UN proper shipping name	TOLUENE SOLUTION
14.3. Transport hazard class(es)	3
Subsidiary class(es)	-
14.4. Packing group	II

14.5. Environmental hazards No
Tunnel restriction code D/E
Labels required 3
14.6. Special precautions Not available.
for user

RID

14.1. UN number UN1294
14.2. UN proper shipping TOLUENE SOLUTION
name
14.3. Transport hazard 3
class(es)
Subsidiary class(es) -
14.4. Packing group II
14.5. Environmental hazards No
Labels required 3
14.6. Special precautions Not available.
for user

ADN

14.1. UN number UN1294
14.2. UN proper shipping TOLUENE SOLUTION
name
14.3. Transport hazard 3
class(es)
Subsidiary class(es) -
14.4. Packing group II
14.5. Environmental hazards No
Labels required 3
14.6. Special precautions Not available.
for user

IATA

14.1. UN number UN1294
14.2. UN proper shipping TOLUENE SOLUTION
name
14.3. Transport hazard 3
class(es)
Subsidiary class(es) -
14.4. Packing group II
14.5. Environmental hazards No
Labels required Not available.
ERG Code 3L
14.6. Special precautions Not available.
for user

IMDG

14.1. UN number UN1294
14.2. UN proper shipping TOLUENE SOLUTION
name
14.3. Transport hazard 3
class(es)
Subsidiary class(es) -
14.4. Packing group II
14.5. Environmental hazards
Marine pollutant No
Labels required Not available.
EmS F-E, S-D
14.6. Special precautions Not available.
for user

14.7. Transport in bulk This substance/mixture is not intended to be transported in bulk.
according to Annex II of
MARPOL 73/78 and the IBC
Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 143/2011 Annex XIV Substances Subject to Authorisation

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Toluene (CAS 108-88-3)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Not regulated.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding

Toluene (CAS 108-88-3)

Other EU regulations

Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances

Not regulated.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Toluene (CAS 108-88-3)

Directive 94/33/EC on the protection of young people at work

Toluene (CAS 108-88-3)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended and respective national laws implementing EC directives. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006 as amended.

National regulations

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work. Pregnant women should not work with the product, if there is the least risk of exposure. Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

DNEL: Derived No-Effect Level.
PNEC: Predicted No-Effect Concentration. PBT: Persistent, bioaccumulative and toxic. vPvB: Very Persistent and very Bioaccumulative. DSD: Directive 67/548/EEC.
CLP: Regulation No. 1272/2008.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R11 Highly flammable.
R38 Irritating to skin.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R67 Vapours may cause drowsiness and dizziness.
H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H361d - Suspected of damaging the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.

Training information

Follow training instructions when handling this material.

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.