

SAFETY DATA SHEET

1. Identification

Product identifier	L-190 PRP SEALANT	
Other means of identification		
Product code	900-0011	
Recommended use	Industrial Leak Sealant.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Company name	Team Industrial Services, Inc.	
Address	200 Hermann Drive, Alvin, Texas 77511	
Telephone	Not available.	
E-mail	Not available.	
Emergency phone number	CHEMTREC - 24 HOURS:	800-424-9300 (USA)
	International:	+1 703-527-3887 (Collect)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Skin corrosion/irritation	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (Central Nervous System)
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging the unborn child. May cause damage to organs (Central Nervous System) through prolonged or repeated exposure. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe gas/mist/vapors/spray.

Response In case of fire: Use appropriate media for extinction. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage Store in a well-ventilated place. Keep container tightly closed.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) Static accumulator - Static accumulating flammable materials can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite material and vapor may cause flash fire (or explosion).

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Dichlorodimethylsilane polymer with dichlorodiphenylsilane, trichlormethylsilane and trichlorophenylsilane	28630-33-3	30-60
Toluene	108-88-3	30-60

Composition comments All concentrations are in percent by weight.

4. First-aid measures

Inhalation	Move to fresh air. Get medical attention if any discomfort occurs.
Skin contact	Remove contaminated clothing and shoes. Flush thoroughly with water for at least 15 minutes. If irritation occurs, get medical assistance.
Eye contact	Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.
Ingestion	Rinse mouth thoroughly with water and give large amounts of milk or water, if person is conscious. Never give anything by mouth to a victim who is unconscious or is having convulsions. Only induce vomiting at the instruction of medical personnel. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Get medical attention immediately.
Most important symptoms/effects, acute and delayed	Skin irritation. Irritation of eyes and mucous membranes. Symptoms include itching, burning, redness, and tearing of eyes.
Indication of immediate medical attention and special treatment needed	Be aware that symptoms of chemical pneumonia (shortness of breath) may occur several hours after exposure.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	No restrictions known.
Specific hazards arising from the chemical	Solvent vapors may form explosive mixtures with air. By heating and fire, corrosive vapors/gases may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Fire fighting equipment/instructions	In the event of fire, cool tanks with water spray. Move containers from fire area if you can do it without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	The product is highly flammable, and explosive vapor/air mixtures may be formed.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Ventilate closed spaces before entering. Avoid inhalation of vapors and contact with skin and eyes. Wear appropriate protective equipment and clothing during clean-up. See Section 8 of the SDS for Personal Protective Equipment.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. After removal flush contaminated area thoroughly with water. Never return spills to original containers for re-use. This material and its container must be disposed of as hazardous waste.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling

Pregnant or breastfeeding women must not handle this product. Avoid inhalation of vapors and contact with skin and eyes. Use only with adequate ventilation. Wear approved safety goggles. Wear protective gloves and appropriate clothing to prevent skin contact. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	560 mg/m ³
		150 ppm
	TWA	375 mg/m ³
		100 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

No exposure standards allocated.

US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety goggles.

Skin protection

Hand protection

Wear protective gloves. Polyvinyl alcohol gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing to prevent any possibility of skin contact.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Private clothes and working clothes should be kept separately.

9. Physical and chemical properties

Appearance	Colorless liquid.
Physical state	Liquid.
Form	Liquid.
Color	Colorless.
Odor	Solvent.
Odor threshold	0.5 - 23 ppm (Toluene)
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	230 °F (110 °C) (solvent)
Flash point	< 50.0 °F (< 10.0 °C) Setflash
Evaporation rate	1 (Butyl acetate=1)
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.2
Flammability limit - upper (%)	7
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	6 mm Hg @ 68°F
Vapor density	Not available.
Relative density	0.9
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Flames and sparks.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon monoxide. Carbon dioxide. Silicon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Vapors may cause drowsiness and dizziness.
Skin contact	Causes skin irritation. Prolonged or repeated contact may dry skin and cause dermatitis. Components of the product may be absorbed into the body through the skin.
Eye contact	May cause eye irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Skin irritation. Irritation of eyes and mucous membranes. Symptoms include itching, burning, redness and tearing. Be aware that symptoms of chemical pneumonia (shortness of breath) may occur several hours after exposure.

Information on toxicological effects

Acute toxicity	Causes skin and eye irritation. May cause central nervous system effects. May cause discomfort if swallowed.		
Components	Species	Test Results	
Toluene (CAS 108-88-3)			
Acute			
<i>Dermal</i>			
LD50	Rabbit	14.1 ml/kg	
<i>Inhalation</i>			
LC50	Rat	49000 mg/m ³ , 4 Hours	
<i>Oral</i>			
LD50	Rat	636 mg/kg	
Skin corrosion/irritation	Causes skin irritation. Prolonged or repeated contact may dry skin and cause dermatitis.		
Serious eye damage/eye irritation	May cause eye irritation.		
Respiratory or skin sensitization			
Respiratory sensitization	Not classified.		
Skin sensitization	Not a skin sensitizer.		
Germ cell mutagenicity	Not classified.		
Carcinogenicity	Not classified.		
IARC Monographs. Overall Evaluation of Carcinogenicity			
Toluene (CAS 108-88-3)		3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)			
Not listed.			
Reproductive toxicity	Suspected of damaging the unborn child.		
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.		
Specific target organ toxicity - repeated exposure	May cause damage to the following organs through prolonged or repeated exposure: Central nervous system.		
Aspiration hazard	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.		
Chronic effects	Danger of serious damage to health by prolonged exposure. Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain.		
Further information	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.		

12. Ecological information

Ecotoxicity	The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
--------------------	--

Components	Species	Test Results
Toluene (CAS 108-88-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Pink salmon (Oncorhynchus gorboscha) 6.86 - 8.48 mg/l, 96 hours
Persistence and degradability	No data available.	
Bioaccumulative potential	No data available on bioaccumulation.	
Partition coefficient n-octanol / water (log Kow)		
Toluene (CAS 108-88-3)	2.73	
Mobility in soil	Expected to be mobile in soil.	
Mobility in general	The product has poor water-solubility. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.	
Other adverse effects	Not available.	

13. Disposal considerations

Disposal instructions	Dispose of this material and its container to hazardous or special waste collection point. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 °F
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	UN1294
UN proper shipping name	TOLUENE SOLUTION
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	No
Special precautions for user	Not available.
Special provisions	IB2, T4, TP1
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN1294
UN proper shipping name	TOLUENE SOLUTION
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No
ERG Code	3L
Special precautions for user	Not available.

IMDG

UN number	UN1294
UN proper shipping name	TOLUENE SOLUTION
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No
EmS	F-E, S-D
Special precautions for user	Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200 (OSHA) and 8 CCR § 5194 (Cal/OSHA).
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Toluene (CAS 108-88-3)

LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
 Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Toluene	108-88-3	30-60

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US state regulations WARNING: This product contains chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Toluene (CAS 108-88-3)

US. Rhode Island RTK

Toluene (CAS 108-88-3)

US. California Proposition 65**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Toluene (CAS 108-88-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	17-February-2015
Revision date	-
Version #	01
Further information	HMIS® is a registered trade and service mark of the NPCA. I - Safety Glasses, Gloves, Dust, Vapor Respirator
HMIS® ratings	Health: 2* Flammability: 3 Physical hazard: 0 Personal protection: I

NFPA ratings



List of abbreviations

References	ACGIH EPA: Acquire database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
------------	---

Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available.
------------	--